

FARMTRAC

ENGINEERED FOR AN UNSTOPPABLE PERFORMANCE

FARMTRAC
COMPACT 20



**Power-Packed
with 3-Cylinder**



**Master Control With
9 F + 3 R Constant Mesh
Transmission**



**Lift Heavy with Ease –
800 kg Capacity**

FARMTRAC 20 (4WD)

ENGINE	Make	Mitsubishi
	No. of Cylinders	3
	Tractor Horsepower	18
	Displacement (cc)	952
	Rated RPM	2700
	Emission Norms	Stage V
	Aspiration	Natural Aspiration
	Fuel tank capacity (Ltrs.)	24
	Air cleaner	Dry Type
TRANSMISSION	Gear	9 F + 3 R
	Type	Constant Mesh
REAR AXLE	Type	Bull Gear Reduction
	Differential Lock	Yes
SPEED : FORWARD (KM/H) MAX./MIN		Max. 18.4 / Min. 1.2
CLUTCH TYPE		Single Clutch
BRAKE TYPE		OIB
PTO	Speed (rpm)	540 @ 2504
	Type	Dual PTO
3-POINT HITCH		CAT I N
STEERING	Type	Power Steering
HYDRAULIC	Control system	Position & Draft Control
	Lift Capacity - at lower link end (kg)	800 kg
	Standard auxiliary valve	1DA/SA Convertible with Detent
TYRE	Front Tyre	6 * 12
	Rear Tyre	8.3 * 20
DIMENSIONS (+/-2%)	Overall length (mm)	2674
	Overall width (mm)	1041 (Agri) 1413 (Turf, Ind.)
	Overall height (mm)	2196
	Wheel base (mm)	1420
OPTIONAL FEATURES		
Rear wheel weight		No
Front weight		No
Front weight Carrier		Hanger
Driver seat		E-Marked with Seat Belt
Rear tow hook		No
Swinging draw bar		Yes
ROPS		Yes
Canopy		No
Safety Start Switch Neutral - Gear		Yes
Battery		No
Tyre Options		Industrial, Agriculture, Radial, Turf

Farmtrac International Business Division

15/5, Mathura Road, Faridabad (NCR), India | Phone: +91-129-2575507/5292

Website: www.escortskubota.com | E-mail: ekl_ex.internationalbusiness@escortskubota.com

Follow Us:  Farmtrac Tractors  farmtrac_worldwide  Farmtrac Worldwide

Disclaimer: Product specifications and features are subject to changes due to continuous development.



Scan for more details